

Print!S

more **Social**, more **Print!** S



Print!S is the ideal printer for kitchen-tickets, receipts and documents, designed specifically for the Retail and Hospitality markets

Has the form of a cube, and it is possible to install it horizontally or vertically. It is the perfect solution for a Point of Sale, thanks to its compact design and connectivity. In fact, it has Ethernet, LAN and ESB ports: the Ethernet port, in particular, allows a high speed connection, while also insuring communication security and an easy wiring, avoid all problems connected with distance through a wireless connection via IP address.

RCH 80mm automatic thermal printer now comes to you at a very friendly price!



Print! S



HARDWARE

Printer	High resolution graphic thermal printer
Printing speed	250 mm/s
High resolution	576 dots/ line - 8 dots/ mm
Paper roll	79,5 mm +/- 0.5 mm
Diameter	max 83 mm
Changing the paper roll	easy loading
Paper cutter	Partial cut
Interfaces	1 RS 232 serial port 1 RJ11 port per cash drawer, 12V 1 Ethernet 1 USB Device
Sensor	paper out (roll finished), print head temperature, printer cover open
Software Driver	Windows X86 / X64 / Linux /OPOS
Dimensions	L138 x P175x H120 mm
Weight	1320 g
Power Supply	Input: AC 110V~220V, 50~60HZ Output: DC 24V/2.5A
Operating Conditions	Temperature: 0 ~ 45 °C Humidity: 10 ~ 80%
Reliability	Automatic cutter 1 million cuts Printing head 150Km

SOFTWARE

Customizable graphic functions Possibility to print different font, for a maximum of 48 characters for each line

- **Features** Supports ESC/POS commands
 - · Possibility to use it both as kitchen ticket printer and receipt/invoice printer with continuous paper
 - · Command to open 24V cash drawer

Characters per line

12×24dots up to 48 Characters per line

Characters

- ANK font
- Font A: 12 × 24dots
- Font B: 9 × 17dots
- · Traditional Chinese Character: 24×24dots

Languages

PAN European Languages (ENG, SPA, FRE, DEU...), Asian Languages: Chinese,

Jap, Korean

supported

Barcodes UPC-A/ UPC-E/ JAN13(EAN13)/ JAN8(EAN8)/ CODE39/ ITF/ CODABAR/ CODE93/ CODE128/QRCODE

Communication Compatible with EPSON ESC/POS protocol and STAR command sets





INTERFACES

0000

SFRIAI

ETHERNE"

DRAWE

OPTIONS

Wif

21/10/16 rev.00